

DYNAMIC CHECKWEIGHTER CW-600G

- This checkweigher is suitable for standard applications in food and other industries ;
- System can store 100 product options for a wide variety of open or closed products in food and industrial production environments ;
- System can be intergrated with metal detector.

Multiple industrial application



Food



Chemical



Accessories



100-600g

Weighing range



±0.5g

Accuracy



200 +Pcs/min

Speed



Standard specification

Model	CW-600G
Weighing range	100~600g
Scale division	0.5g
Highest Accuracy(3 σ) *	± 0.1 g
Highest Weighing speed *	200 pcs/min
Belt speed	5~60 m/min
Belt size	310×250mm
Weighing platform Height **	Length: 50~240mm Width: 20~150mm Height: 10~180mm
Tested object size	750±50mm
Belt material	PVC (white)
Structure of the material	Carbon steel, SS304 stainless steel (weighing platform)
Alarm light	3-color signal light (Red, yellow, green) , Optional buzzer
Display size	10-inch color touch screen
Rejector lineup	Options: swing type, push type or lift up type rejector
Power	AC 220V, 50/60Hz, 300W
operating temperature	0~40°C
IP grade	IP54

* Depend on the weight, size, and material of test object. Test accuracy: **0.5g at 200pcs/min**

Dimensions

Unit:mm

