

DYNAMIC CHECKWEIGHER CW-1.2K

- For pouches, bags, and soft-sided containers, bottles;
- S304 stainless steel frame is standard;
- 10 inch touch screen, can store over 1 million transaction, data export through USB;
- High speed at 150 pcs per min, with 0.5 gram.

Multiple industrial application







Grain



Chemical



100-1200g

Weighing range



±1g
Accuracy



120_{+Pcs/min}
Speed



Standard specification	
Model	CW-1.2K
Weighing range	100~1200g
Scale division	0.1g
Highest Accuracy(3σ) *	±1 g
Highest Weighing speed *	120 pcs/min
Belt speed	5~50 m/min
Belt size	400×250mm
Weighing platform Height **	Length: 50~300mm Width: 20~220mm Height: 10~220mm
Tested object size	750±50mm
Belt material	PU (white)
Structure of the material	SS304 stainless steel
Alarm light	3-color signal light(Red, yellow, green),Optional buzzer
Display size	10-inch color touch screen
Rejector lineup	Options: swing type, push type rejector
Power	AC220V单相,50/60Hz,300W
operating temperature	0~40℃
IP grade	IP54

^{*} Depend on the weight, size, and material of test object. Test accuracy: 1g at 120pcs/min

Dimensions Unit:mm





