

# DYNAMIC CHECKWEIGHTER CW-600G

- This checkweigher is suitable for standard applications in food and other industries;
- System can store 100 product options for a wide variety of open or closed products in food and industrial production environments;
- System can be intergrated with metal detector.

## Multiple industrial application



Food



Chemical



Accessories



**10-600g**

Weighing range



**±0.5g**

Accuracy



**200** +Pcs/min

Speed



## Standard specification

Model	CW-600G
Weighing range	10~600g
Scale division	± 0.1g
Highest Accuracy(3 $\sigma$ ) *	0.5g
Highest Weighing speed *	200 pcs/min
Belt speed	5~60 m/min
Belt size	310×250mm
Weighing platform Height **	750±50mm
Tested object size	Length: 50~240mm Width: 20~150mm Height: 10~180mm
Belt material	PVC (white)
Structure of the material	Carbon steel, SS304 stainless steel (weighing platform)
Alarm light	3-color signal light (Red, yellow, green) , Optional buzzer
Display size	10-inch color touch screen
Rejector lineup	Options: swing type, push type or lift up type rejector
Power	Single Phase AC-220V ±10%, 50/60HZ
operating temperature	0~40°C
IP grade	IP54

\* Depend on the weight, size, and material of test object. Test accuracy: **0.5g at 200pcs/min**

## Dimensions

Unit:mm

