

VERTICAL CHECKWEIGHER CW-60K-V

CW-60K-V checkweigher has wide weighing range but high accuracy guarantee. It is perfect for weighing the various bags and boxes running in vertical way in the production line.

- Standard module design for easy installation and maintenance;
- Easy integrating in the production line;
- Weighing range: 5~60kg, weighing accuracy is within ±20g;

Multiple applications









Standard




Economy Type


Specification		
Model	CW-60K-V Standard	CW-60K-V Economy Type
Power	AC220V±10%, 50/60Hz, 1KW	AC220V±10%, 50/60Hz, 1KW
Weighing Range	5~60kg	5~60kg
Best Accuracy*	±10g	±20g
Highest Speed*	≤50pcs/min	≤30pcs/min
Tested Object Size	Length: 100~600mm,	Length: 100~600mm,
	Width: 50~400mm	Width: 50~400mm
	Height: 50~600mm	Height: 50~600mm
Belt Speed	40m/min	22m/min
Conveyor Size	800mm*400mm	800mm*400mm
Distance Between Rollers	800mm	800mm
Weighing Platform Height	400 (±50mm)	400 (±50mm)
Structure Material	Carbon Steel, SS304 (weighingPlatform)	Carbon Steel, SS304 (WeighingPlatform)
Belt Material	PVC (black)	PVC (black)
Display	10-inch touch screen	7-inch touch screen
Working Temperature	0~40℃	0~40℃
Max. Humidity	90% R.H, non-condensation	90% R.H, non-condensation
Load Limit	The instantaneous load limit is 100kg	The instantaneous load limit is100kg


^{*}It depends on the features of tested object, such as size and weight.

DimensionsUnit:mm

Standard







Economy Type

