


DYNAMIC CHECKWEIGHER CW-6K

- CW-6K check weigher is suitable for product weight range from 0.5-6kg.
- Weighing accuracy is within $\pm 2g$;
- 10-inch touch screen, can store over 1 million transaction, data export through USB;
- It is widely used for food, feeds, logistic industries, automation production line, and so on.

Multiple industrial application



Feeds



Logistic



Automation production line



0.5-6kg
Weighing range



$\pm 2g$
Accuracy



100 $+Pcs/min$
Speed



Standard specification

Model	CW-6K
Weighing range	0.5~6kg
Scale division	0.5g
Best Accuracy(3 σ)*	± 2 g
Highest Weighing speed *	100pcs/min
Belt speed	10~50m/min
Belt size	500*400mm
Weighing platform Height **	750 $\pm$ 50mm
Tested object size	Length100~420mm, Width50~400mm, Height50~400mm
Belt material	PVC
Structure of the material	Carbon steel, SS304 for weighing platform
Alarm light	3-color signal light (Red, yellow, green)
Display size	10-inch color touch screen
Rejector lineup	Options: swing type, push type
Power	AC220V single phase, 50/60Hz, 850W
operating temperature	0~40°C
IP grade	IP54,IP65 Optional

*Depend on the weight, size and material of test object.

Dimensions

Unit:mm

