

DUPLEX PACKING FILLER AF-01K II



50g-1kg
Weighing range



Stable
Performance



Easy
Installation

± 2g
Best Accuracy



Pneumatic
Cylinder Control



High Speed
Weighing

3600 Pcs/h
Highest Speed



Feature

- **High speed and accuracy:**
the highest speed can reach 3600pcs/h and the best accuracy is $\pm 2g$;
- **Granular materials:**
special designed for small weighing range packages, like rice, millet, beans and so on.
- **Stable performance:**
step motor + vibrator feeding-type, pneumatic discharging-type;
- **Parameter setting:**
self-adjust function with target value set only, easy operation.



Specification

Model	PaxGo AF-01K II
Weighing Range	0.05~1kg
Division	1g
Best Accuracy	±2g
The Highest Speed	3600pcs/h
Volume	2.8L*2
Communication	USB, 2*RS485
Air supply	0.4~0.6MPa 2m ³ /h
Environment	0°C~40°C, 90%R.H, No condensation
Power	AC220V±10%, 50/60Hz, 400W
Feeding/Discharging	Step motor + vibrator feeding-type, pneumatic discharging-type;
Material	Carbon steel/stainless steel optional

* Normally, the diameter of the testing material 1-5mm.

Structure & Dimension

Unit: mm

