


# DYNAMIC CHECKWEIGHER CW-6K

- CW-6K check weigher is suitable for product weight range from 0.5-6kg.
- Weighing accuracy is within  $\pm 2g$ ;
- 10-inch touch screen, can store over 1 million transaction, data export through USB;
- It is widely used for food, feeds, logistic industries, automation production line, and so on.

## Multiple industrial application



Feeds



Logistic




Automation production line



**0.5-6kg**  
Weighing range



**$\pm 2g$**   
Accuracy



**100**  $+Pcs/min$   
Speed



## Standard specification

Model	CW-6K
Weighing range	0.5~6kg
Scale division	0.5g
Best Accuracy(3 $\sigma$ )*	$\pm 2$ g
Highest Weighing speed *	100pcs/min
Belt speed	10~50m/min
Belt size	500*400mm
Weighing platform Height **	750 $\pm$ 50mm
Belt material	PU ( white )
Structure of the material	Carbon steel, SS304 for weighing platform
Alarm light	3-color signal light ( Red, yellow, green )
Display size	10-inch color touch screen
Rejector lineup	Options: swing type, push type
Power	AC220V single phase, 50/60Hz, 850W
operating temperature	0~40°C
IP grade	IP54,IP65 Optional

\*Depend on the weight, size and material of test object.

## Dimensions

Unit:mm

