





PACKING FILLER (3 load cells structure) AF-25K



5-25 kg
Weighing range

± 15g
Best accuracy

1150 Pcs/h
Top speed



Features:


- **Granular material:** design for plastic particle, granular fertilizer, feeds and other granular material.
- **Easy dismounting:** module design of measuring hopper for easy cleaning;
- **Parameter setting:** self-adjust function with target value set only;
- **Stable performance:** servo motor controls feeding process;
- **Fast and accurate:** weighing range is 5-25kg. Speed can reach 1150 pcs/h, and best accuracy $\pm 15g$.



Optional:



- SS304 stainless steel.



Specification

Model	PaxGO AF-25K (3 load cells structure)
Weighing range	5~25Kg
Division	1g
Best Accuracy*	$\pm 15g$
Top speed*	1150pcs/h
Volume	55L
Feeding method	Feeding control by servo, pneumatic discharging
Material	SS304, carbon steel
I/O	8 output(5V), 8 input(24V)
Communication	RS485, Modbus TCP/IP
Pneumatic	0.4~0.6MPa
Power	Single Phase AC-220V $\pm 10\%$, 50/60HZ, 1KW
Working environment	0~40°C, 90%R.H condensation is not allowed

*Speed and accuracy depend on the density and flow rate of the materials.

Structure & Dimension

Unit: mm

