

# DYNAMIC CHECKWEIGHER

## CW-60K For Cement Industry


CW-60K special version is a dynamic checkweigher with wide weighing range and high accuracy. The special structure design and components improve the protection performance and durability, for dusty industrial field.

### Feature Highlights


- PVK belt and thick machine frame are wear-resistant;
- Omron diffuse reflection photoelectric on the top position avoiding dust;
- Automatic air blowing device to regularly clean up the dust on the photoelectric to ensure its use properly;
- Synchronous wheel quenching to enhance the durability and increase the lifespan.



Thickened belts



Quenching treatment



Automatic air blowing



**60kg**  
Maximum capacity



**±10g**  
Best accuracy



**60 Pcs/min**  
Highest speed



### Standard specification

Model	CW-60K For cement industry
Maximum capacity	60kg
Scale division	5g
Best accuracy*	±10g
Highest weighing speed*	60pcs/min
Belt speed	10~60m/min
Belt size	1000/1200 x600mm
Weighing platform height*	400~750+100mm/-50mm
Belt material	PVK(black)
Structure of the material	Carbon steel, S304 stainless steel are optional
Alarm light	3-color signal light (Red, yellow, green),Optional buzzer
Display size	10-inch color touch screen
Rejector lineup	Options: roller push type
Power	AC 200~240V, 50/60Hz, 825W
Operating temperature	0~40°C
IP grade	IP54/IP65 Optional

\*Depend on the weight, size and material of test object.

### Dimensions

Unit: mm

