GENERAL MEASURE TECHNOLOGY CO.,LTD

DYNAMIC CHECKWEIGHER CW-60K

- Heavy load heavy duty, for bags ,boxes weight up to 60kg with accuracy within 10 grams;
- Strong structure for hash environment, option S304 S316 structure, option stainless loadcell;
- Using 4 loadcells for plat form, with variable mounting position for high accuracy under ruff environment;
- Flexible Modbus communication to integrate with computer, scanner, dimension measure device and soon.

Multiple industrial application







Automation

Grain and feeds



60kg Maximum capacity



±10g
Best accuracy



60 Pcs/min
Highest speed



| Standard specification | |
|---------------------------|--|
| Model | CW-60K |
| Maximum capacity | 60Kg |
| Scale division | 5g |
| Best accuracy* | ±10g |
| Highest weighing speed* | 60pcs/min |
| Belt speed | 10~60m/min |
| Belt size | 1000/1200×600mm |
| Weighing platform height* | 400~750+100mm/-50mm |
| Structure of the material | Carbon steel, S304 stainless steel (weighing platform) |
| Alarm light | 3-color signal light(Red, yellow, green),Optional buzzer |
| Display size | 10-inch color touch screen |
| Rejector lineup | Options: roller push type |
| Belt material | PVC (black) |
| Power | Single Phase AC-220V ±10%, 50/60HZ ,825W |
| Operating temperature | 0~40°C |
| IP grade | IP54,IP65 Optional |

^{*}Depend on the weight, size and material of test object.

Unit:mm

Dimensions

