Weighing automation technology GENERAL MEASURE TECHNOLOGY CO..LTD

Specification

Weighing range

Accuracy range*

Model

Division

Top speed*

DUPLEX PACKING FILLER AF-50KII



10-50_{kg} Weighing range





Stable Performance

Easy Installation

±10~25g Accuracy range





Servo Motor Control

1800 Pcs/h

Features:

- Granular material: design for packing plastic particles, rice, sugar and other granular material;
- Easy dismounting: module design of measuring hopper for easy cleaning;
- Parameter setting: self-adjust function with target value set only;
- Stable performance: servo motor controls feeding process;
- Fast and accurate: weighing range is 10-50kg, Speed can reach 1800 pcs/h, and accuracy range ± 10~25g.

Optional:




User-friendly interface design, vivid display, easy to operate.












Volume	86L x 2
Feeding method	Feeding control by servo, pneumatic discharging
Material	SS304,carbon steel
I/O	8 output(5V),8 input(24V)
Communication	RS485,Modbus TCP/IP
Pneumatic	0.4~0.6MPa
Power	Single Phase AC-220V ±10%,50/60HZ,1KW
Working environment	0~40°C, 90%R.H condensation is not allowed
	*Accuracy and speed depends on the material characteristics and packing weight.
Structure & Dimension Unit: mm	




PaxGO AF-50KII


10~50Kg

±10~25g

1800pcs/h

2g





^{*}Specification and dimension may be upgraded, please consult sales manager for the latest info.