

GRANULE PACKING FILLER AF-5K



0.25-5kg
Weighing range



Stable
Performance



Easy
Installation

±1~5g
Accuracy range



Servo Motor
Control



Weighing
Accurate

1500 Pcs/h
Top speed

Features:

- **Granular material:** design for rice, millet, beans and other granular material;
- **Easy dismounting:** module design of measuring hopper for easy cleaning;
- **Parameter setting:** self-adjust function with target value set only;
- **Stable performance:** servo motor controls feeding process;
- **Fast and accurate:** weighing range is 0.25-5kg, Speed can reach 1500 pcs/h ,and accuracy range ± 1~5g.



- User-friendly interface design, vivid display, easy to operate.




Specification

Model	PaxGO AF-5K
Weighing range	0.25~5Kg
Division	1g
Accuracy range*	±1~5g
Top speed*	1500 pcs/h
Volume	12L
Feeding method	Servo motor+feeding vibrator , pneumatic discharging
Material	SS304,carbon steel
I/O	8 output(24V),8 input(24V)
Communication	RS485, Modbus TCP/IP
Pneumatic	0.4~0.6MPa
Power	Single Phase AC-220V ±10%,50/60HZ,500W
Working environment	0~40℃ , 90%R.H condensation is not allowed

*Accuracy and speed depends on the material characteristics and packing weight.

Structure & Dimension

Unit: mm



*Specification and dimension may be upgraded, please consult sales manager for the latest info.